



VTI manufactures many different types of doors and openings to suit your needs, featuring battle tested frames with high quality paint, heavy duty components, lockable handles, and a safety lock back latch system that secures the door in open position. All door systems are designed for use in daily tactical training environments, will be installed with the frames and attaching hardware to allow for the standard movements of each door.



Standard Pre-Hung Doors

We provide a 3'x 6' 8" as well as a 3'x 7' single swing pedestrian door. All door systems are capable of using a standard commercially available solid-core steel door. One slab is provided pre-hung with each door system installed in a structure. These door systems come standard with our innovative lock-back system ensuring added safety during training operations.

Our standard doors (pre-hung lock-back system) are 3" thick at the throat of the door jamb and the door itself is 1.75" thick if equipped with non-explosive, non-breaching commercial assembly lock. We have alternate door systems that use commercial locks that allow non-explosive breaching which are 2.25" thick with steel insulated pre-hung slabs available via common commercial sources.



Breach Doors

Our standard breaching doors (pre-hung lock-back system) are 3" thick at the throat of the door jamb and the door itself is 1.75" thick if equipped with non-explosive, breaching assembly (replaceable).

We provide breaching door systems identical to the standard pre-hung door in sizes 3' x 6' 8" as well as a 3' x 7' single swing pedestrian door. Our breaching doors include field-replaceable inserts made of either plywood or steel designed to allow fast replacement of sacrificial areas around the door handle and locking assemblies. These door systems come standard with our innovative lock-back system ensuring added safety during training operations.



Roll-Up Doors

All roll-up doors are designed for daily operation, provide solid weather seals, and are installed with roll-up area encased to ensure operational safety during rapid use. Trim details and other cosmetic items are designed to withstand tactical use. Painted surfaces are selected from our PMA color choices with finish type to match overall structure exterior.

We provide 4', 5', 6' and 8' widths with 3', 6', 7' and 8' heights. Other sizes are possible if requested. We will provide the exact size specified in the individual MOUT structures and will allow the Customer to substitute within those sizes are required. We are aware that current solicitation specifies 60" (5') to 72" (6') wide by 72" (6') to 84" (7') high. We will meet the specific MOUT design specification.



Courtyard Doors

Courtyard doors will be A36 steel or equivalent. The exterior courtyard doors will be 4' wide and will be capable of being hinged to courtyard walls or the corners of MOUT structures using bolt-on kits. Courtyard doors are available in heights of 4' or 8' and will be painted "Desert Tan". These door systems include a lock-back assembly allowing the door to be secured in both the full open position and full closed position. All hardware meets section "3.8 Materials/commercial components" requirements of VTI-InterPod Product Support and Operations Manual.

Create Your Own Mobile Immersive Training Environment (MITE)